

PCIDM[®] V3

Modem for Dismounted or Highly Mobile Systems



Description

32-bit two-channel network interface PCMCIA card.

Supports digital radios.

When coupled with a radio, sends interoperable digital data information to a variety of military assets.

Enables the sharing of accurate and timely information.

Enables existing PC-based applications to extend their capability.

Uses

- Close Air Support
- Situational Awareness and Command and Control Networks
- Tactical Air Control Party (TACP)
- Joint Terminal Attack Controller (JTAC)

Software Development Kit

- Software Development Kit: provides users with application development and integration tools
- Network Monitoring Tool
- AMPGUI™: graphical user interface that assists users in configuring the PCIDM.

Interoperable

- F-16
- F/A-18
- AH-64D
- OH-58D
- AV-8B
- AFATDS
- Blue Force Tracking (BFT)
- C2PC
- C2CE
- PFED
- UAVs into BFT
- JSTARS
- Tornado
- Eurofighter
- JSF

Attributes

Channels

- Two

Link Layer Protocols

- AFAPD
- TACFIRE
- MTS
- IDL
- MIL-STD-188-220
- MIL-STD-188-184
- RAW Mode

Network Layer Protocols

TCP/IP (IP, UDP, TCP, ICMP, SNMP)

Application Message Sets

- AFAPD
- MIL-STD-6017 VMF
- TACFIRE
- MTS
- IDL

VMF

- MIL-STD-2045-47001
- MIL-STD-188-220
- Internet Protocol
- N-layer Pass Through
- CAS

MIL-STD-188-184

- IP Routing Support
- Emails
- Notes

Radio Interfaces (Digital)

Radios (Examples)

- PRC-117F
- PRC-148 MBITR/JEM
- PRC-152
- RT-1523E (SINGARS)
- PSC-5
- ARC-201D
- ARC-210
- KY-58
- KY-57
- KY-100
- Other custom radio interfaces

Baseband Modulations

- NRZ
- PACKET (X.21)

Host Support

Device Drivers

- Windows (XP, 2000)

Key Features

Size

- PCMCIA Type II
- 54mm W
- 81mm D
- 5mm H

Power

+3.3V, 0.4A, 1.3W
Typical

Weight

4 oz (113.4g)

Temperature

-40 to 85 C

Elbit Systems of America, C4I Solutions
8200 Greensboro Drive, Suite 700
McLean, VA 22102
703.893.2007
www.elbitsystems-us.com